












SOLAR - BATTERY & ELECTRIC FRIDGES AND FREEZERS - SUPER EFFICIENT







   	FRIDGE-FREEZER		FREEZER - CAN BE USED AS COOLER				
	ATSL45	ATSL55	ATLC40C	ATLC90H	ATL-C140	ATLC-190	ATLC-265
							
Gross capacity	45 L.(38L. +7L.)	55 L.(42L. + 11 L.)	40 L.	90 L.	140 L.	190 L.	265 L.
Voltage	DC 12v or DC24v	DC 12v or DC24v	DC12v or DC24v	DC12v or DC24v	DC12v or DC24v	DC12v or DC24v	DC12v or DC24v
Average power consumption	60w	62w	60w	65w	72w	78w	82w
Temperature range	at +32°C drop to -18°C, adjustable via ELECTRONIC CONTROL . Thermostat with digital temperature display		at +32°C drop to -18°C, adjustable thermostat . Optional, external digital temperature display				at +32°C drop to -18°C, adjustable thermostat . Optional, external digital temperature display
Insulation	Good insulation for reducing consumption. CFC-free polyurethane foam						Good insulation for reducing consumption. CFC-free polyurethane foam
System	Fully hermetic compressor with integrated control electronics, low-voltage protection adjustable by user or Electronic battery starter, electronic fuse/automatic reverse pole protection, aluminium roll-bond evaporator		Fully hermetic compressor with integrated control electronics, low-voltage protection adjustable by user or Electronic battery starter, electronic fuse/automatic reverse pole protection, tube-on-sheet evaporator				Fully hermetic compressor with integrated control electronics, low-voltage protection adjustable by user or Electronic battery starter, electronic fuse/automatic reverse pole protection, tube-on-sheet evaporator
Material	precoated sheet or stainless steel\ Aluminium\PP/abs	precoated sheet or stainless steel/ABS	stainless steel/coated sheet/prepainted	stainless steel/coated sheet/prepainted	stainless steel/coated sheet/prepainted	stainless steel/coated sheet/prepainted	stainless steel/coated sheet/prepainted
Colour	grey or customer required color		white or customer required color			white	white or silver
Weight	approx.23kg/26kg	approx.25kg/28kg	approx.18kg/20kg	approx.38kg/40kg	approx.40kg/42kg	approx.46kg/48kg	approx.47kg/50kg
Special features	direct connect to DC12V or DC 24v,two different refrigeration/freezer compartments,anti discharge battery protect.automatic turn off when low voltage,special wind lane to adjust temperature of refrigeration compartment. Detachable lid		direct connect to DC12V or DC 24v,anti discharge battery protect.automatic turn off when low voltage.				direct connect to DC12V or DC 24v,anti discharge battery protect.automatic turn off when low voltage.
Accessory	OPTIONAL:AC/DC ADAPTOR/PROTECTIVE BAG BASKET		OPTIONAL:AC/DC ADAPTOR				OPTIONAL:AC/DC ADAPTOR
loading quantity	120pcs/20FQ 252PCS/40HQ	90pcs/20FQ 252PCS/40HQ	575PCS/40HQ	98/20` FCL - 228PCS/40`FCL	52 units/20fcl 136PCS/40`FCL	36 units/20fcl - 100PCS/40HQ	32 units/20fcl & 90PCS/40HQ
carton dimension	745*545*570	745*545*630	506*465*535	685*560*950	885*560*950	1000*580*930	1108*675*990
Size	650*450*480	650*450*540	475*450*520	626*556*900	815*555*900	955*520*900	1055*680*950

TROPICALIZED

ALL PRODUCTS ARE MANUFACTURED ACCORDING TO CE & ROHS EUROPEAN QUALITY STANDARD . ORIGIN: SPAIN/EUROPE

SOLAR - BATTERY & ELECTRIC FRIDGES AND FREEZERS - SUPER EFFICIENT

DOUBLE DOOR REFRIGERATOR + FREEZER

	ATL-D120	ATLD145	ATLD160	ATLD180	
	 				
Gross capacity	120 L.(42L. freezer,78 L. fridge)	145 L.(42L. freezer,103 L. fridge)	160 L.(60L. freezer,100 L. fridge)	190 L.(62L. freezer,128 L. fridge)	
Voltage	DC 12v or DC24v	DC 12v or DC24v	DC 12v or DC24v	DC 12v or DC24v	
Average power consumption	72w	72w	75w	76w	
Temperature range	at +32°C drop to -18°C, adjustable thermostat . Optional, external digital temperature display				
Insulation	Good insulation for reducing consumption. CFC-free polyurethane foam		Good insulation for reducing consumption. CFC-free polyurethane foam		
System	Fully hermetic compressor with integrated control electronics, low-voltage protection adjustable by user or Electronic battery starter, electronic fuse/automatic reverse pole protection.		Fully hermetic compressor with integrated control electronics, low-voltage protection adjustable by user or Electronic battery starter, electronic fuse/automatic reverse pole protection.		
Material	precoated sheet /coated sheet				
Colour	silver grey	silver grey	silver grey	silver grey	
Weight	approx.36kg/41kg	approx.38kg/43kg	approx.45kg/52kg	approx.48kg/55kg	
Special features	direct connect to DC12V or DC 24v,anti discharge battery protect.automatic turn off when low voltage.				
Accessory	OPTIONAL:AC/DC ADAPTOR	OPTIONAL:AC/DC ADAPTOR	OPTIONAL:AC/DC ADAPTOR	OPTIONAL:AC/DC ADAPTOR	
loading quantity	84 UNITS /20FCL - 184PCS/40HQ	62 units/20fcl - 182PCS/40HQ	52/20fcl - 136PCS/40HQ	52/20fcl & 134PCS/40HQ	
carton dimension	530*590*1230	530*590*1355	560*610*1365	560*610*1520	
Size	445*540*1200	445*545*1330	499*550*1300	499*550*1460	