

Professional Solar fountains

- Great for a garden waterfall or fountain feature
- Oxigenates water
- No wiring
- Easy installation
- Environment-friendly

6V DC solar fountain pump: The lifted water height is up to 200L/h,

Ideal for a garden waterfall or fountain feature.

* It can be set up easily wherever desired without the need for batteries or wiring installation.

* Perfect for creating a new fountain, waterfall anywhere in the pond, yard or patio.

* Includes 1/3 different fountain nozzles for different fountain shapes.

* Replace your present electric power with our solar pump kit to make your fountain more environment-friendly, more portable and safer for your kids.



SPECIFICATIONS ATL-f201

Voltage range	6-9V DC	Removable foam filter	yes
Min.Max.Pumping height	0.5-0.9 m	Fountain nozzles	3 pcs
Max. liters per hr	200	Connection cable length	5m
Recommended solar panel	1.5W	Dimensions L, W, H (mm)	70x38x60
Delivery side (discharge) thread :	Ø8mm	Guarantee	2 year
Salt or Fresh water use :	yes		

Performance:

Liters/ Head per hour								
Sun condition	0m	0.5m	0.75m	1.0m	1.5m	2.0m	3.0m	Max Height
Low	150	0						0.5m
Medium	175	80	0					0.75m
Full	200	130	90	0				0.9m

Professional Solar fountains

- **Luxury model**
- **Great for a garden waterfall or fountain feature**
- **Oxygenates water**
- **No wiring**
- **Easy installation**
- **Environment-friendly**



12-24V DC solar fountain pump: The lifted water height is up to 1550L/h, great for a garden waterfall or fountain feature.

It can be set up easily wherever desired without the need for batteries or wiring installation.

Perfect for creating a new fountain, waterfall anywhere in the pond, yard or patio.

Includes 3 different fountain nozzles for different fountain shapes.

Replace your present electric power with our solar pump kit to make your fountain more environment-friendly, more portable and safer for kids.

SPECIFICATIONS ATL-F1500

Voltage range	12-24V DC	Salt or fresh water use	yes
Max. pumping height	3m	Fountain nozzles	3 pcs
Max. liters per hour	155	Connection cable length	5m
Recommended solar panel	18W	Dimensions L, W, H (mm)	128x58x83
Delivery side (discharge) thread :	ø15mm	Guarantee	3 years
Salt or Fresh water use :	yes		

ROHS **CE**
COMPLIANT
ISO9001

Liters/ Head per hour

Sun condition	0m	0.5m	0.75m	1.0m	1.5m	2.0m	3.0m	Max Height
Low	950	480	290	0				0.9m
Medium	1300	1000	840	630	320	0		1.9m
Full	1550	1300	1200	1050	780	500	50	3.0m