



Poly Crystalline Solar Panel
(30W 18V, IP65)



Lithium ion battery Pack
(15Ah 11.1V IP65)



WiFi IP Camera HD 1080P
(12V 2A)

Model No. ATL-IP925 Characteristics

Image Sensor: 1/2.8" SONY CMOS Sensor
 Resolution: 2.0 Megapixel(1080P=1920*1080)
 Illumination Color 0.01 Lux@F1.2(AGC on), B&W 0.00 Lux@F1.2(IR on)
 Lens Mount Built-in 3MP 3.6mm Fixed Lens
 IRLED Built-in 5:36pcs IR LED
 IR Distance 30M (Night Vision) . System PAL / NTSC
 Resolution Main Stream: 1920*1080;Second Stream:1920*960;Third Stream: 640*480,320*240;
 JPEG Video Bitrate Q720P:640*352;QQ720P:320*176;Special For Mobile Phone View
 Frame 2.0MP and below 25fps(50HZ),30fps(60HZ);CBR/VBR adjustable
 Video Processing H.265+ video coding, support dual stream, AVI format; code stream 32~6144kpbs adjustable
 Support 3DNR,Support Digital WDR, Support JPEG Snapshot
 Image Setting Brightness, contrast, saturation, exposure, up and down inversion, left and right mirror adjustable
 Network Interface 1*RJ45 Ethernet interface,10/100M self-adaption;
 Audio Built-in Microphone and Speaker
 Network Protocol TCP/IP,HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, PPPoE, NTP, UPnP™, SMTP, IPv6, IPv4
 Storage TF Card (Max 128G)
 Motion Detection: 4 independent detection areas can be set (sensitivity 1-100 can be set)
 Action with alarm: Send the alarm picture to the designated mailbox; Alarm upload pictures and videos to FTP server
 Sim Card Support 2G/3G/4G
 Type of network FDD-LTE, TDD-LTE, WCDMA/HSPA+, TD-SCDMA, GSM/GPRS/EDGE
 Operating Frequency LTE B1/B3/B8/B38/B39/B40/B41 - WCDMA 2100/900MHz.TD-SCDMA B34/B39 -TD-SCDMA B34/B39— GSM/GPRS/EDGE: 900/ 1800MHz
 Speed FDD-LTE/TDD-LTE:UP 50M /Down 150Mbps
 HSPA+:UP 5.76M /Down 21Mbps
 TD-SCDMA:UP 2.2Mbps /Down 2.8Mbps
 USIM/SIM Micro SIM Card
 WIFI Protocol 802.11b/g/n (Max 72Mbps Speed) . CMS HiP2P
 Function: Configure by WEB, OSD (on screen display), real-time video transmission, motion detection and IO alarm linkage ,centre prompt and picture pop-up after IO alarm; support remote surveillance client software; support mobile monitoring (iPhone, Android).
 S/N Ratio >=50dB
 ES 1/50 -1/10,000S
 White Balance Auto Tracking White Balance
 Working Temp. Outdoor:-40C to +60C. Humidity 0 to 95% RH . Consumption 450mA .Voltage 12V DC
 Gross weight: 5 Kg. Volume: 0.029cbm/kit. Packing: 12 units/master carton. Gross weight master carton: 60 Kg. Volume: 0.35 cbm